

Thank you! for buying "*The Stopper*"!
Get ready for better tone and more power!

The Performance Products *Flute plug* is a wonderful product that replaces the existing head cork. It is a Delrin material with dual O- rings. Never wears out!

Improves ANY headjoint and any flute!

Dear fellow flute enthusiast;

Performance Flute Plug can be installed in any flute. It replaces the standard "wine bottle cork" stopper. It uses 2 o-rings to effect the airtight seal.

The function of the stopper is twofold.

1. Airtight seal.

2. Dampening the vibrating air column to achieve a pleasant flute sound.

The traditional "wine bottle cork" stopper dampens the vibrating air column MORE than is necessary.

Performance flute plug SETS FREE the vibrating air column to give you more power, cleaner sound, easier and quicker response throughout the full range of the instrument.

Unleash your sound!

All the best,

Bob bob@leitholdmusic.com

Bob Ogren, Designer - Performance Flute Plug and Woodlight Head Joints

QUICK INSTALLATION:

1. Push old head cork assembly out of head joint.
2. Install Performance Plug bottom to top, threaded side up.
(Apply Vaseline sparingly to O-rings to ease installation.)

DETAILED DIRECTIONS FOR INSTALLATION:

You will need an 8" length of PVC pipe.

Use it to push or drive out the old head cork assembly.

Drive it out from top to bottom as the head joint is smallest at the crown end and larger at the end where it goes into the flute body.

Make a mark on the PVC pipe, 17.3 mm from the end.

This mark will show in the center of the embouchure hole when the Performance Flute Plug is in the correct position.

Lubricate the o-rings with a tiny amount of vaseline or cork grease.

Install Performance Flute Plug from bottom to top with the threaded rod up, 17.3 mm from center of embouchure to end of stopper.

The crown screws onto the threaded rod. Use a little clear fingernail polish on the threads to prevent the crown from vibrating loose.

You can also use teflon tape for this.

Good luck, and enjoy!

